

EDC-KBD1

Home | Security | Recording | Accessories

EDC-KBD1
System Keyboard with 3-axis Joystick, 12VDC,

Art-Nr. 74088



Main Features

Programming and control of camera series:
Fastrax and Minitrax
For DVR series DLR1.2, DLR3/4, DTR, DIR and DPR
Supports up to 254 cameras
Joystick control of PTZ functions

Programmable sequences and patterns
Preset position and pattern control
Auto and random scanning
Auxiliary operation

Specifications

Integrated monitor	-
Weight	approx. 1.2kg
Video input	-
Supply voltage	12VDC (connection to the Junction box, 230VAC PSU included)
Site control (direct mode operation)	Keys select cameras and monitors, operates up to 254 presets, 4 patterns, 8 scans. Capability to incorporate up to 300 of presets, patterns, scan and tour itself in up to 8 tours. Camera functions: pan, tilt, zoom, focus, iris for fixed or variable speed control of the camera series Fastrax, Minitrax. Auxiliaries and sequences.
Baud rate	2.400 ~230.000
Interface	3x RS-485, RJ45 (8-pin). 1x KBD (For connection of the junction box: Dome camera series Fastrax), 1x DVR (Recorder series DLR, DTR, DPR)
Remote control	Control of up to 254 Fastrax and/or Minitrax dome cameras, camera series Almira. Up to 99 Digital Video recorders of the series DLR and DTR

EDC-KBD1

(Continuation Specifications)

LCD display	16x2 characters
Power consumption	Approx. 5 watts
Temperature range	0 ~+50°C
Dimensions (HxWxD)	96 (incl. Joystick) x380x168mm
Parts supplied	System keyboard, Junction box with connection cable and PSU
Certificates	CE

SLD Security & Communications
The Old Forge, Ockham Lane, Ockham, Surrey GU236PH England
Phone +44.1483225633 · Fax +44.1483225634
sales@sld.co.uk · www.sld.co.uk

