

## Board Cameras

1/3" B/W Cylinder Camera with 3,6mm

Lens, 12VDC, 420TVL, 0,65Lux

EDP-No.: 91866

### VK-1319

- CCD B&W Cylinder Camera with Integrated Lens
- 1/3" Super HAD CCD Sensor
- Resolution of 420 Horizontal Lines
- Automatic Shutter Control (AES)
- H & V Aperture (APC)
- Internal Synchronization
- High Sensitivity of 0.65 Lux (F2.0)
- Supply Voltage: 12 VDC
- Weatherproof Aluminium Housing
- Mounting Stand with Swivel Head



### Specifications:

Imager	1/3" Sony Super HAD Interline Transfer CCD
System	CCIR
Synchronization	Internal
Sensitivity at 50% video signal	0.65 Lux at F2.0 (VT measurement result)
Horizontal resolution	420 TV lines
Active picture elements	Approx. 290,000 (H) 500 x (V) 582
Gamma correction	0.45
Automatic gain control (AGC)	Yes
Integrated lens	F 2.0/3.6 mm
Video output	1 Vp-p, VBS, 75 ohms
Supply voltage	12 VDC (+/- 10%)
Power consumption	1.2 Watts
Temperature range	-10°C to +50°C
Protection rating	IP67
Housing	Aluminium
Dimensions (LxD)	60x19 mm
Colour	Black
Weight	55 g (incl. stand)

<b>Accessories</b>	
<b>EDP No. / Type</b>	<b>Description</b>
40061 H0820M	F2,0/8mm Board Camera Lens, 1/3", M12X0,5
70442 VT-PS12DC-3	Power Supply 230VAC/12VDC(500mA), stabilized
77779 VT-PS12DC-UK	Plugable PSU 12VDC-500mA, stabilized with UK mains plug, open DC lead
40065 H1225	F2.5/12mm Board camera lens 1/3", M12x0.5mm
40072 H0620M	F2.0/6mm Board camera lens 1/3", M12x0.5