

SC-19



A value 19" surveillance display with rapid response time, quick signal-switching and robust video support for security and control centre environments.

For a cost-effective surveillance display solution, look no further than the AG Neovo SC-19. A bright, high resolution full colour screen with quick signal-switching and 3ms response time ensures sharp, smooth video playback. Looping BNC video inputs and NTSC/PAL support maximise flexibility for system integration. And with built-in speakers, stylishly slim profile and VESA mountability, the SC-19 will look just as attractive as its amazingly affordable price.

- > High 1280 × 1024 SXGA resolution
- > Anti-Burn-in™ technology
- > Video inputs (BNC in x 1, BNC out x 1)
- > Looping video inputs for multiple connections
- > Quick signal-switching time (≤ 0.8 sec.)
- > NTSC/PAL auto-detection
- > Selectable signal source
- > PC compatible
- > Built-in speakers
- > Key lock function
- > Auto-adjustment for optimal setting
- > Security socket
- > VESA standard wall mount



SC-19

| Specifications | | SC-19 |
|----------------------|-----------------------------|--|
| Panel | Panel Type | TFT LCD |
| | Panel Size | 19.0" (483mm) |
| | Max. Resolution | SXGA 1280 x 1024 |
| | Pixel Pitch | 0.294 mm |
| | Brightness | 300 cd/m ² (Typical) |
| | Contrast Ratio | 1000:1 (Typical) |
| | Viewing Angle (H/V) | 170°/160° (Typical) |
| | Display Colour | 16.7M |
| | Response Time | 3 ms (GTG) |
| Frequency (H/V) | | H: 31 kHz - 80 kHz V: 50 Hz - 75 Hz |
| Max. Pixel Clock | | 140 MHz |
| Input | Analogue | D-Sub via DVI-VGA cable |
| | Digital | 29-Pin DVI-I |
| | BNC Security | BNC Connector in / out |
| Audio | Audio In | 3.5 mm Audio Line-in |
| | Speaker | 1W x 2 |
| Power | AC-DC Adaptor | External |
| | Power | AC 100-240 V, 50-60 Hz |
| | Consumption | < 39 W (On) < 1.5 W (Off) |
| Plug & Play | VESA | DCC 2B |
| Operating Conditions | Temperature | 0 °C ~ 40 °C |
| | Humidity | 10% ~ 85% |
| Storage Conditions | Temperature | -20 °C ~ 60 °C |
| | Humidity | 10% ~ 95% |
| Mounting | VESA FPMPMI | Yes (100 mm) |
| Tilt | Tilt | -5° ~ +15° |
| Dimensions | Product (W x H x D) | 420 x 406 x 190mm (16.8" x 16.2" x 7.6") |
| | Packaging (W x H x D) | 461 x 489 x 164mm (18.1" x 19.3" x 6.5") |
| | | |
| Weight | Product Weight | 5.5 kg (12.1 lbs) |
| | Packaged Weight | 5.7 kg (12.5 lbs) |
| Regulation Approval | Certifications & Compliance | UL/CUL, CB, FCC, CE, BSMI, WEEE, RoHS |
| Accessories | Supplied | CD ROM (user manual and drivers), power cord, power adaptor, 29-Pin DVI-I cable, DVI-VGA cable, CVBS BNC connector cable |



Stylish and slim design ideal for professional security environments



Built-in speakers enable more rigorous security monitoring



Looping video inputs allow multiple display connections



Video versatility, including VGA, DVI and BNC In/Out

SLD Security & Communications
 The Old Forge, Ockham Lane, Ockham, Surrey GU236PH England
 Phone +44.1483225633 · Fax +44.1483225634
 sales@sld.co.uk · www.sld.co.uk